



ABC LIOVIN



CME 95HT

KEY SPECS

- Width - 8'
- Length - 36' 1/2"
- Folded Height - 12' 3/4"
- Mast - Up 38' 1/2"
- Retract/Down Pressure - 62,830 lbs/33,135 lbs
- Rotary Torque 37,277 ft/lbs - 65 RPM

LEARN MORE

info@abcdrilling.com

Phone: + 1 (562) 9818575

Web: abcdrilling.com

This is the most powerful HSA rig available. It was purpose built with a unique High Torque Rotary Drive designed to turn 24" diameter augers. The result is significantly more torque than a standard CME 95.

CAPABILITIES

- Hollow Stem Auger / Mud / Air / Rotary / Wireline Coring Drill Rig
- 75" stroke, hydraulic vertical drive system
- Retract rate up to 96 ft/min with Fine Hydraulic Feed Control
- Four forward gears and Four reverse with power shift transmission
- Moyno 3L8 water/grout pump with high/low gearing
- Coated 470 gallon water tank
- Hydraulic Auger Rack capable of carrying 130' of 4 1/4" ID or 60' of 6 1/4" ID Augers
- Three hydraulic leveling jacks for stability during drilling
- Calibrated above ground SPT auto-hammer for geotechnical sampling